



NOTES

- A. $\frac{1}{2}$ " ZINC HIGH DOME ACORN NUT - ITEM #461 B&F FASTENER SUPPLY (OR EQUAL)
- B. $\frac{1}{2}$ " x $1\frac{3}{8}$ " ZINC WASHER
- C. FLAT-STYLE 4-WAY SIGN SEPARATOR (COMPATIBLE WITH ITEM F)
- D. 2-PANEL 9" STREET SIGN NOTCH & PUNCH E450 COMPLIANT WITH 4-WAY SEPARATOR BRACKET
- E. LOCKING-STYLE 4-WAY SIGN SEPARATOR (COMPATIBLE WITH ITEM F)
- F. 4-WAY ($2\frac{3}{8}$ " DIAMETER) ROUND CAP-STYLE #556 BY TRAFFIC SAFETY COMPANY
- G. $\frac{1}{2}$ " ZINC THREADED ROD, LENGTH AS FOLLOWS:
 - 2-9" SIGNS = 21" ROD
 - 3-9" SIGNS = 30" ROD
- H. $\frac{1}{4}$ "-20-1/2" HEX HEAD BRASS BOLT WITH $\frac{1}{4}$ "-20 HEX HEAD BRASS NY-LOCK NUT
- I. ALL THREADED CONNECTION SHALL BE ANTISIEZED (EXCEPT FOR BRASS NUTS AND/OR BOLTS)

2" O.D. ROUND SIGN POST



CITY OF BURNSVILLE - ENGINEERING DEPT.
**STREET SIGN PLATE
 ASSEMBLY DETAIL**

Plate No.	STR-24
Revision Date	3/2019
File Location: S:\Details\english\Street\STR24-Street Sign Plate Assembly.dwg	